



# CAL-NEVA SUPPLY CO., INC.

1900 MARINA BLVD. SAN LEANDRO, CA 94577  
PHONE: 510-895-6506 FAX: 510-895-9694

## DATA SHEET

### **NEOPRENE/EPDM/SBR (Self-Extinguishing) Economy Blend**

**4216-S**

Color:		Black
Specifications:	ASTM D-1056-00	2A2
	ASTM D-1056-67 <sup>(1)</sup>	SCE 42
	SAE J18-02	2A2
	GM 6086M <sup>(3)</sup>	II
	GMN11106 <sup>(3)</sup>	II
25% Compression Deflection (PSI)		5 - 9
Shore 00 Durometer (Approximate)		40 - 60
Density (Approximate p.c.f.)		4 1/2 - 6 1/2
Water Absorption By Weight		5%
Temperature Range		-70 to 158 F
Weather Resistance:	UV	Fair
	Ozone	Good
Accelerated Linear Shrinkage (Typical)		5%
Tensile Strength (Typical)		50 PSI
Elongation (Typical)		150%
Flammability:	FM VSS No. 302	Pass
	UL 94 HBF	Pass ( <i>UL Listed</i> )
UL Recognized Component Gasket Materials: (Call Customer Service for Details)		File No. JMST2

**ISO 9001-2000 Certified**